

## Hydraulic tappet additive (Hydro-Stößel-Additiv)

**DESCRIPTION** High performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning again.

**PROPERTIES**

- improves the lubrication properties of the oil
- cleans valve bores
- suitable for use in vehicles with turbochargers and vehicles with catalytic converters
- prevents engine noises caused by hydraulic tappets

**TECHNICAL DATA**

Color	: yellowish	
Appearance	: viscous liquid	
Density at +20 °C	: 0.895 g/cm <sup>3</sup>	DIN 51757
Viscosity at +40 °C	: 510 mm <sup>2</sup> /s	DIN 51562

**AREAS OF APPLICATION** For all gasoline and diesel engines. Can be mixed with all commercially available motor oils

**APPLICATION** One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change.

**Note:**  
**Not suitable for use on motorbikes with wet clutches.**

**AVAILABLE PACK SIZES**

Hydraulic tappet additive	300 ml	Part no.	1009
---------------------------	--------	----------	------

PI 02/01/04

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

